

HC

Perfect for residential projects, the HC controller provides smart water savings and remote irrigation management capabilities.

KEY BENEFITS

- Number of stations:
 - 6 or 12 (fixed indoor)
- Standard programming option allows for 6 independent irrigation programs and 6 start times per program
- Advanced programming option provides station-based programming with up to 6 total start times available
- 24-hour maximum station run time provides flexibility for low-flow zones
- 2 sensor inputs available for use with any Klik sensors and HC Flow Meter
- Station outputs can also be used to activate a pump start relay or master valve
- Wi-Fi enabled for quick connection to Hydrowise® software
- 2¾" full-color touchscreen display for simple programming at the control panel
- Built-in milliamp sensor for wire fault detection and alerts (12-station model only)

OPERATING SPECIFICATIONS

- Transformer input: 120 VAC
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- Approvals: UL, cUL, FCC, CE, RCM
- Warranty period: 2 years

USER-INSTALLED OPTIONS

- Wireless HC Flow Meter option permits wireless flow monitoring for Hydrowise enabled systems


HC	
Model	Description
HC-600i	Fixed 6-station, plastic indoor wall mount
HC-1200i	Fixed 12-station, plastic indoor wall mount



HC

(plastic indoor)
Height: 6"
Width: 7"
Depth: 1¼"

Compatible with:



HC Flow Meter



Rain-Clik
Sensor



Soil-Clik
Sensor



EPA WaterSense Approved

Recognized as a responsible water-saving tool by the U.S. Environmental Protection Agency