



A turbulent flow, Pressure Compensating dripper available in 3 flows.

### Features

- Take-Apart for easy inspection and cleaning.
- Self-flushing action with insect baffle to minimise blockages.
- PC barbed dripper range: 2 lph, 4 lph and 8 lph with 4 mm spout.
- Also available with 3 mm and 4 mm barb outlets.
- Coloured bases to identify flow rates.
- 4 lph PC Spike and In-Line Spike models to anchor CETA® at the plant.

### Applications

Pots, planter boxes, balcony patio and landscape applications.



CETA®  
PC 4 lph  
Spike 4 mm

CETA®  
PC 4 lph  
In-Line Spike 4 mm

Performance	DISCHARGE (lph)		
	2 lph	4 lph	8 lph
PRESSURE (kPa)			
50	1.9	3.3	6.2
100	2.0	3.8	7.9
150	2.2	4.2	7.9
200	2.3	4.4	8.1
250	2.3	4.4	8.1
300	2.3	4.4	8.0
350	2.2	4.3	7.8
MINIMUM CROSS SECTION (mm)	0.7 x 0.6	0.8 x 0.8	1.2 x 0.9

\* C, for all CETA® PC emitters conforms to ISO 9261

### CETA® PC

NOMINAL FLOW	BASE COLOUR	ORDER CODE	PACK QUANTITY	PACKS PER CARTON	CARTON (kg)
2 lph	Red	30425	100	70	13.3
4 lph	Black	30445	100	70	13.3
8 lph	Green	30485	100	70	13.3

### CETA® PC with 3 mm Barb Outlet

NOMINAL FLOW	BASE COLOUR	ORDER CODE	PACK QUANTITY	PACKS PER CARTON	CARTON (kg)
2 lph	Red	30515	100	60	13.5
4 lph	Black	30525	100	60	13.5
8 lph	Green	30535	100	60	13.5

### CETA® PC with 4 mm Barb Outlet

NOMINAL FLOW	BASE COLOUR	ORDER CODE	PACK QUANTITY	PACKS PER CARTON	CARTON (kg)
2 lph	Red	30545	100	60	13.5
4 lph	Black	30555	100	60	13.5
8 lph	Green	30565	100	60	13.5

### CETA® PC 4 lph Spike

BASE TYPE	ORDER CODE	PACK QUANTITY	PACKS PER CARTON	CARTON (kg)
Spike	30625	25	60	9.0
In-Line Spike	30655	25	50	7.7

### Specifications

DIMENSIONS ASSEMBLED		CETA® PC	CETA® PC with 3 mm or 4 mm barb outlet	CETA® PC Spike/In-Line Spike
HEIGHT		25 mm	35 mm	135 mm
WIDTH		20 mm	20 mm	36 mm / 42 mm
DEPTH		16 mm	16 mm	16 mm
WEIGHT (approx)		1.7 g	2.0 g	5.0 g
UV STABILISED MATERIAL	BASE/SPIKE	polypropylene	polypropylene	polypropylene
	CAP	polypropylene	polypropylene	polypropylene
	DIAPHRAGM	silicone rubber	silicone rubber	silicone rubber
	ADAPTOR		acetal	
CONNECTION TYPE: Inlet		BARB 4 mm	BARB 4 mm	BARB 4 mm
Outlet		SPOUT 4 mm	BARB 3 mm or 4 mm	SPOUT 4 mm



CETA®  
PC 2 lph  
Barb 4 mm

CETA®  
PC 4 lph  
Barb 4 mm

CETA®  
PC 8 lph  
Barb 4 mm

CETA®  
PC 2 lph  
Barb 4 mm  
3 mm or 4 mm  
Outlet

CETA®  
PC 4 lph  
Barb 4 mm  
3 mm or 4 mm  
Outlet

CETA®  
PC 8 lph  
Barb 4 mm  
3 mm or 4 mm  
Outlet