

Úderový postřikovač RC 172 (1")



RC 172 - 1", kruhový, pouze hlavní tryska

tryska	tlak		dostřik [m]	průtok			mm/hod čtver.
	[Bar]	[kPa]		[m³/h]	[l/min]	[l/s]	
5,6 mm	2.5	250	14.9	1.86	31.0	0.52	17
	3.0	300	16.0	2.09	34.8	0.58	16
	3.5	350	16.8	2.26	37.7	0.63	16
	4.0	400	17.4	2.42	40.3	0.67	16
	4.5	450	18.0	2.58	43.0	0.72	16
	5.0	500	18.6	2.72	45.3	0.76	16
	5.5	550	19.2	2.86	47.7	0.79	16
6,4 mm	2.5	250	15.9	2.43	40.5	0.68	19
	3.0	300	16.7	2.73	45.5	0.76	20
	3.5	350	17.4	2.96	49.3	0.82	20
	4.0	400	17.6	3.17	52.8	0.88	20
	4.5	450	18.9	3.37	56.2	0.94	19
	5.0	500	19.4	3.56	59.3	0.99	19
	5.5	550	19.8	3.74	62.3	1.04	19
7,2 mm	2.5	250	16.8	3.09	51.5	0.86	22
	3.0	300	17.6	3.46	57.7	0.96	22
	3.5	350	18.4	3.75	62.5	1.04	22
	4.0	400	19.4	4.02	67.0	1.12	21
	4.5	450	20.5	4.27	71.2	1.19	20
	5.0	500	21.5	4.51	75.2	1.25	20
	5.5	550	21.9	4.74	79.0	1.32	20
8,0 mm	2.5	250	18.0	3.75	62.5	1.04	23
	3.0	300	18.4	4.21	70.2	1.17	25
	3.5	350	19.3	4.57	76.2	1.27	25
	4.0	400	20.2	4.91	81.8	1.36	24
	4.5	450	21.1	5.23	87.2	1.45	23
	5.0	500	21.9	5.54	92.3	1.54	23
	5.5	550	22.8	5.83	97.2	1.62	22
9,6 mm	2.5	250	18.3	5.18	86.3	1.44	31
	3.0	300	19.5	5.80	96.7	1.61	31
	3.5	350	20.6	6.32	105.3	1.76	30
	4.0	400	21.9	6.80	113.3	1.89	28
	4.5	450	22.6	7.25	120.8	2.01	28
	5.0	500	23.0	7.68	128.0	2.13	29
	5.5	550	23.5	8.10	135.0	2.25	29



RC 172 - 1", kruhový, dvě trysky

tryska	tlak		dostřik [m]	průtok			mm/hod čtver.
	[Bar]	[kPa]		[m³/h]	[l/min]	[l/s]	
5,2 a 3,2 mm	2,5	250	14,9	2,29	38,2	0,64	21
	3,0	300	16,0	2,54	42,3	0,71	20
	3,5	350	16,8	2,74	45,7	0,76	19
	4,0	400	17,4	2,92	48,7	0,81	19
	4,5	450	17,8	3,08	51,3	0,86	19
	5,0	500	18,1	3,23	53,8	0,90	20
	5,5	550	18,3	3,36	56,0	0,93	20
5,6 a 3,2 mm	2,5	250	14,9	2,53	42,2	0,70	23
	3,0	300	16,0	2,83	47,2	0,79	22
	3,5	350	16,8	3,05	50,8	0,85	22
	4,0	400	17,4	3,27	54,5	0,91	22
	4,5	450	18,0	3,47	57,8	0,96	21
	5,0	500	18,6	3,66	61,0	1,02	21
	5,5	550	19,2	3,83	63,8	1,06	21
6,4 a 3,2 mm	2,5	250	15,9	3,10	51,7	0,86	25
	3,0	300	16,7	3,47	57,8	0,96	25
	3,5	350	17,4	3,75	62,5	1,04	25
	4,0	400	17,6	4,02	67,0	1,12	26
	4,5	450	18,9	4,26	71,0	1,18	24
	5,0	500	19,4	4,50	75,0	1,25	24
	5,5	550	19,8	4,71	78,5	1,31	24
7,2 a 3,2 mm	2,5	250	16,8	3,76	62,7	1,04	27
	3,0	300	17,6	4,20	70,0	1,17	27
	3,5	350	18,4	4,54	75,7	1,26	27
	4,0	400	19,4	4,87	81,2	1,35	26
	4,5	450	20,5	5,16	86,0	1,43	25
	5,0	500	21,5	5,45	90,8	1,51	24
	5,5	550	21,9	5,71	95,2	1,59	24
8,0 a 3,2 mm	2,5	250	18,0	4,42	73,7	1,23	27
	3,0	300	18,4	4,95	82,5	1,38	29
	3,5	350	19,3	5,36	89,3	1,49	29
	4,0	400	20,2	5,76	96,0	1,60	28
	4,5	450	21,1	6,12	102,0	1,70	27
	5,0	500	21,9	6,48	108,0	1,80	27
	5,5	550	22,8	6,80	113,3	1,89	26



Poznámka:

- uvedené srážkové výšky jsou počítány pro výseč 180°
- velikost závitu hlavní trysky 3/8"
- velikost závitu rozprašovací trysky 1/8"