


## Úderový postřikovač RC 170 (1")

RC 170 - 1", kruhový, dvě trysky

tryska	tlak		dostřik [m]	průtok			mm/hod čtver.
	[Bar]	[kPa]		[m <sup>3</sup> /h]	[l/min]	[l/s]	
5,6 a 4,4 mm	2,5	250	18,2	3,00	50,0	0,83	18
	3,0	300	18,7	3,45	57,5	0,96	20
	3,5	350	19,0	3,63	60,5	1,01	20
	<b>4,0</b>	<b>400</b>	<b>19,6</b>	<b>3,97</b>	<b>66,2</b>	<b>1,10</b>	<b>21</b>
	4,5	450	19,9	4,13	68,8	1,15	21
	5,0	500	20,4	4,31	71,8	1,20	21
	5,5	550	21,3	4,60	76,7	1,28	20
6,4 a 4,4 mm	2,5	250	18,9	3,54	59,0	0,98	20
	3,0	300	19,9	4,04	67,3	1,12	20
	3,5	350	20,4	4,26	71,0	1,18	20
	<b>4,0</b>	<b>400</b>	<b>21,1</b>	<b>4,67</b>	<b>77,8</b>	<b>1,30</b>	<b>21</b>
	4,5	450	21,6	4,92	82,0	1,37	21
	5,0	500	22,1	5,13	85,5	1,43	21
	5,5	550	23,0	5,44	90,7	1,51	21
6,4 a 4,8 mm	2,5	250	18,9	3,75	62,5	1,04	21
	3,0	300	19,9	4,26	71,0	1,18	22
	3,5	350	20,4	4,54	75,7	1,26	22
	<b>4,0</b>	<b>400</b>	<b>21,1</b>	<b>4,99</b>	<b>83,2</b>	<b>1,39</b>	<b>22</b>
	4,5	450	21,6	5,19	86,5	1,44	22
	5,0	500	22,1	5,40	90,0	1,50	22
	5,5	550	23,0	5,79	96,5	1,61	22
7,2 a 4,8 mm	2,5	250	19,2	4,29	71,5	1,19	23
	3,0	300	20,4	4,90	81,7	1,36	24
	3,5	350	21,0	5,17	86,2	1,44	23
	<b>4,0</b>	<b>400</b>	<b>21,9</b>	<b>5,72</b>	<b>95,3</b>	<b>1,59</b>	<b>24</b>
	4,5	450	22,4	5,97	99,5	1,66	24
	5,0	500	22,8	6,22	103,7	1,73	24
	5,5	550	23,7	6,62	110,3	1,84	24
7,2 a 5,6 mm	2,5	250	19,5	4,77	79,5	1,33	25
	3,0	300	20,7	5,44	90,7	1,51	25
	3,5	350	21,4	5,76	96,0	1,60	25
	<b>4,0</b>	<b>400</b>	<b>22,6</b>	<b>6,35</b>	<b>105,8</b>	<b>1,76</b>	<b>25</b>
	4,5	450	23,2	6,62	110,3	1,84	25
	5,0	500	23,6	6,90	115,0	1,92	25
	5,5	550	24,6	7,40	123,3	2,06	24
8,0 a 5,6 mm	2,5	250	19,8	5,38	89,7	1,49	27
	3,0	300	20,7	6,15	102,5	1,71	29
	3,5	350	21,4	6,52	108,7	1,81	28
	<b>4,0</b>	<b>400</b>	<b>22,6</b>	<b>7,20</b>	<b>120,0</b>	<b>2,00</b>	<b>28</b>
	4,5	450	23,2	7,52	125,3	2,09	28
	5,0	500	23,6	7,83	130,5	2,18	28
	5,5	550	24,6	8,40	140,0	2,33	28
8,8 a 5,6 mm	2,5	250	19,8	6,04	100,7	1,68	31
	3,0	300	21,6	6,99	116,5	1,94	30
	3,5	350	22,5	7,35	122,5	2,04	29
	<b>4,0</b>	<b>400</b>	<b>23,7</b>	<b>8,08</b>	<b>134,7</b>	<b>2,24</b>	<b>29</b>
	4,5	450	24,4	8,42	140,3	2,34	28
	5,0	500	25,0	8,76	146,0	2,43	28
	5,5	550	26,2	9,37	156,2	2,60	27
9,6 a 5,6 mm	2,5	250	21,1	6,68	111,3	1,86	30
	3,0	300	23,0	7,67	127,8	2,13	29
	3,5	350	23,9	8,06	134,3	2,24	28
	<b>4,0</b>	<b>400</b>	<b>25,1</b>	<b>8,83</b>	<b>147,2</b>	<b>2,45</b>	<b>28</b>
	4,5	450	25,7	9,21	153,5	2,56	28
	5,0	500	26,3	9,58	159,7	2,66	28
	5,5	550	27,6	10,80	180,0	3,00	28



Poznámka:

- uvedené srážkové výšky jsou počítány pro výseč 180°
- velikost závitů dvou hlavních trysek 3/8"